

Sammandrag 38 2023



Oil Pattern Distance38Reverse Brush Drop37Oil Per Board50 ulForward Oil Total12.15 mLReverse Oil Total10.35 mLVolume Oil Total22.5 mLTank ConfigurationOnly ATank A ConditionerTank B Conditioner.

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	4L	4R	1	14	33	0.0	0.0	0.0	1650
2	5L	5R	2	18	62	0.0	5.1	5.1	3100
3	6L	6R	2	18	58	5.1	10.2	5.1	2900
4	8L	8R	2	18	50	10.2	15.3	5.1	2500
5	10L	10R	1	18	21	15.3	17.8	2.5	1050
6	11L	11R	1	22	19	17.8	20.9	3.1	950
7	2L	2R	0	22	0	20.9	32.0	11.1	0
8	2L	2R	0	30	0	32.0	38.0	6.0	0

	CTART	CTOR	LOADS	corro	CROSSER	CTART	FNID		T.O.11
_	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	1.OIL
1	2L	2R	0	30	0	38.0	30.0	-8.0	0
2	9L	9R	1	18	23	30.0	27.5	-2.5	1150
3	7L	7R	2	18	54	27.5	22.4	-5.1	2700
4	5L	5R	2	18	62	22.4	17.3	-5.1	3100
5	4L	4R	1	18	33	17.3	14.8	-2.5	1650
6	3L	3R	1	14	35	14.8	12.9	-1.9	1750
7	2L	2R	0	10	0	12.9	0.0	-12.9	0
ı									

Cleaner Ratio Main Mix NA
Cleaner Ratio Back End Mix NA
Cleaner Ratio Back End Distance NA
Buffer RPM: 4 = 720 | 3 = 500 | 2 = 200 | 1 = 50
Created by SWEBOWL TK(HJ) 230808 Machines without DB use DB 38 For use in Swedish league 2023->

Forward Reverse Combined

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	MIddle: Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	2.58	1.08	1	1	1.08	2.58
(1

