

Sammandrag 39 2025-27



Oil Pattern Distance **Forward Oil Total Tank Configuration**

39 17.95 mL **A Only**

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

37 7.95 mL Valfri Oil Per Board **Volume Oil Total Tank B Conditioner**

50 ul 25.9 mL Valfri

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	14	148	0.0	5.9	5.9	7400
2	6L	6R	2	18	58	5.9	11.0	5.1	2900
3	7L	7R	1	18	27	11.0	13.5	2.5	1350
4	8L	8R	2	18	50	13.5	18.6	5.1	2500
5	10L	10R	2	18	42	18.6	23.7	5.1	2100
6	12L	12R	2	18	34	23.7	28.8	5.1	1700
7	2L	2R	0	22	0	28.8	39.0	10.2	0

2 11L 11R 3 22 57 30.0 20.7 -9.3 28 3 9L 9R 2 18 46 20.7 15.6 -5.1 23 4 7L 7R 1 18 27 15.6 13.1 -2.5 13 5 6L 6R 1 18 29 13.1 10.6 -2.5 14	2 11L 11R 3 22 57 30.0 20.7 -9.3 2850 3 9L 9R 2 18 46 20.7 15.6 -5.1 2300 4 7L 7R 1 18 27 15.6 13.1 -2.5 1350 5 6L 6R 1 18 29 13.1 10.6 -2.5 1450		START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
3 9L 9R 2 18 46 20.7 15.6 -5.1 23 4 7L 7R 1 18 27 15.6 13.1 -2.5 13 5 6L 6R 1 18 29 13.1 10.6 -2.5 14	3 9L 9R 2 18 46 20.7 15.6 -5.1 2300 4 7L 7R 1 18 27 15.6 13.1 -2.5 1350 5 6L 6R 1 18 29 13.1 10.6 -2.5 1450	1	2L	2R	0	30	0	39.0	30.0	-9.0	0
4 7L 7R 1 18 27 15.6 13.1 -2.5 13 5 6L 6R 1 18 29 13.1 10.6 -2.5 14	4 7L 7R 1 18 27 15.6 13.1 -2.5 1350 5 6L 6R 1 18 29 13.1 10.6 -2.5 1450	2	11L	11R	3	22	57	30.0	20.7	-9.3	2850
5 6L 6R 1 18 29 13.1 10.6 -2.5 14	5 6L 6R 1 18 29 13.1 10.6 -2.5 1450	3	9L	9R	2	18	46	20.7	15.6	-5.1	2300
		4	7L	7R	1	18	27	15.6	13.1	-2.5	1350
	6 2L 2R 0 18 0 10.6 0.0 -10.6 0	5	6L	6R	1	18	29	13.1	10.6	-2.5	1450
6 2L 2R 0 18 0 10.6 0.0 -10.6		6	2L	2R	0	18	0	10.6	0.0	-10.6	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



ltem	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.57	1.3	1	1	1.3	3.57



