

Oil Pattern Distance	44	Reverse Brush Drop	38	Oil Per Board	50 ul
Forward Oil Total	14.65 mL	Reverse Oil Total	12.45 mL	Volume Oil Total	27.1 mL
Tank Configuration	A Only	Tank A Conditioner	Fire	Tank B Conditioner	FIRE

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	3L	3R	1	14	35	0.0	0.0	0.0	1750
2	4L	4R	2	18	66	0.0	5.1	5.1	3300
3	6L	6R	2	18	58	5.1	10.2	5.1	2900
4	8L	8R	2	18	50	10.2	15.3	5.1	2500
5	10L	8R	2	18	46	15.3	20.4	5.1	2300
6	14L	13R	2	18	28	20.4	25.5	5.1	1400
7	16L	15R	1	22	10	25.5	28.6	3.1	500
8	2L	2R	0	22	0	28.6	38.0	9.4	0
9	2L	2R	0	30	0	38.0	44.0	6.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	0	44.0	30.0	-14.0	0
2	16L	13R	1	18	12	30.0	27.5	-2.5	600
3	14L	11R	2	18	32	27.5	22.4	-5.1	1600
4	10L	8R	3	14	69	22.4	16.5	-5.9	3450
5	5L	5R	1	14	31	16.5	14.6	-1.9	1550
6	4L	4R	1	14	33	14.6	12.7	-1.9	1650
7	3L	3R	1	14	35	12.7	10.8	-1.9	1750
8	2L	2R	1	14	37	10.8	8.9	-1.9	1850
9	2L	2R	0	14	0	8.9	0.0	-8.9	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

For use in Swedish playoffs 2025.
 Created by SWEBOWL TK(W) 250505.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3:24	1:57	1:1	1:02	1:31	3:24

