



Sammandrag 41 2025-27




Oil Pattern Distance	41	Reverse Brush Drop	41	Oil Per Board	50 ul
Forward Oil Total	12.75 mL	Reverse Oil Total	12.45 mL	Volume Oil Total	25.2 mL
Tank Configuration	A Only	Tank A Conditioner	Valfri	Tank B Conditioner	Valfri

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	10	74	0.0	1.4	1.4	3700
2	7L	7R	1	14	27	1.4	3.3	1.9	1350
3	10L	10R	3	14	63	3.3	9.2	5.9	3150
4	11L	11R	3	18	57	9.2	16.8	7.6	2850
5	12L	12R	2	18	34	16.8	21.9	5.1	1700
6	2L	2R	0	18	0	21.9	28.0	6.1	0
7	2L	2R	0	26	0	28.0	34.0	6.0	0
8	2L	2R	0	30	0	34.0	41.0	7.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	41.0	34.0	-7.0	0
2	13L	13R	1	18	15	34.0	31.5	-2.5	750
3	12L	12R	2	18	34	31.5	26.4	-5.1	1700
4	11L	11R	2	18	38	26.4	21.3	-5.1	1900
5	10L	10R	2	18	42	21.3	16.2	-5.1	2100
6	9L	9R	2	18	46	16.2	11.1	-5.1	2300
7	2L	2R	2	14	74	11.1	7.2	-3.9	3700
8	2L	2R	0	10	0	7.2	0.0	-7.2	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.24	1.77	1	1	1.77	5.24

