

Oil Pattern Distance	46	Reverse Brush Drop	43	Oil Per Board	50 uL
Forward Oil Total	17.3 mL	Reverse Oil Total	12.85 mL	Volume Oil Total	30.15 mL
Tank Configuration	A Only	Tank A Conditioner	Your choice	Tank B Conditioner	Your choice

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	14	111	0.0	3.9	3.9	5550
2	10L	10R	2	18	42	3.9	9.0	5.1	2100
3	12L	12R	2	18	34	9.0	14.1	5.1	1700
4	2L	2R	2	18	74	14.1	19.2	5.1	3700
5	14L	14R	2	22	26	19.2	25.4	6.2	1300
6	2L	2R	1	22	37	25.4	28.5	3.1	1850
7	15L	15R	2	22	22	28.5	34.7	6.2	1100
8	2L	2R	0	22	0	34.7	46.0	11.3	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	22	0	46.0	36.0	-10.0	0
2	15L	15R	3	18	33	36.0	28.4	-7.6	1650
3	14L	14R	2	18	26	28.4	23.3	-5.1	1300
4	13L	13R	2	18	30	23.3	18.2	-5.1	1500
5	11L	11R	3	18	57	18.2	10.6	-7.6	2850
6	2L	2R	3	18	111	10.6	3.0	-7.6	5550
7	2L	2R	0	14	0	3.0	0.0	-3.0	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Created by SWEBOWL TK(HJ) 250618. Machines without db use db 46.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3	2.29	1.12	1.12	2.29	3

