

Oil Pattern Distance	40	Reverse Brush Drop	40	Oil Per Board	50 ul
Forward Oil Total	15.25 mL	Reverse Oil Total	10.5 mL	Volume Oil Total	25.75 mL
Tank Configuration	A Only	Tank A Conditioner	Your choice	Tank B Conditioner	Your choice

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	18	74	0.0	2.5	2.5	3700
2	5L	5R	2	18	62	2.5	7.6	5.1	3100
3	10L	10R	3	18	63	7.6	15.2	7.6	3150
4	10L	10R	4	22	84	15.2	27.6	12.4	4200
5	15L	15R	2	22	22	27.6	33.8	6.2	1100
6	2L	2R	0	26	0	33.8	40.0	6.2	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	22	0	40.0	32.0	-8.0	0
2	15L	15R	2	22	22	32.0	25.8	-6.2	1100
3	10L	10R	3	18	63	25.8	18.2	-7.6	3150
4	10L	10R	3	18	63	18.2	10.6	-7.6	3150
5	5L	5R	2	18	62	10.6	5.5	-5.1	3100
6	2L	2R	0	18	0	5.5	0.0	-5.5	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Created by SWEBOWL TK(HJ) 250618

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.23	1.67	1.07	1.07	1.67	5.23

