


Oil Pattern Distance	39	Reverse Brush Drop	39	Oil Per Board	50 ul
Forward Oil Total	19.7 mL	Reverse Oil Total	6.4 mL	Volume Oil Total	26.1 mL
Tank Configuration	Only A	Tank A Conditioner		Tank B Conditioner	

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	14	148	0.0	5.9	5.9	7400
2	4L	4R	2	18	66	5.9	11.0	5.1	3300
3	6L	6R	2	18	58	11.0	16.1	5.1	2900
4	8L	8R	2	18	50	16.1	21.2	5.1	2500
5	10L	10R	2	18	42	21.2	26.3	5.1	2100
6	12L	12R	1	18	17	26.3	28.8	2.5	850
7	14L	14R	1	18	13	28.8	31.3	2.5	650
8	2L	2R	0	22	0	31.3	39.0	7.7	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	22	0	39.0	22.0	-17.0	0
2	13L	13R	1	18	15	22.0	19.5	-2.5	750
3	11L	11R	1	18	19	19.5	17.0	-2.5	950
4	10L	10R	1	18	21	17.0	14.5	-2.5	1050
5	9L	9R	2	18	46	14.5	9.4	-5.1	2300
6	7L	7R	1	18	27	9.4	6.9	-2.5	1350
7	2L	2R	0	14	0	6.9	0.0	-6.9	0



Cleaner Ratio Main Mix                    NA            Forward  
 Cleaner Ratio Back End Mix            NA            Reverse  
 Cleaner Ratio Back End Distance      NA            Combined  
 Buffer RPM: 4 = 720 | 3 = 500 | 2 = 200 | 1 = 50  
 Created by Swebowl TK 220808

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	Middle:Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	3.03	1.33	1.01	1.01	1.33	3.03

