

Oil Pattern Distance	40	Reverse Brush Drop	40	Oil Per Board	50 ul
Forward Oil Total	15.8 mL	Reverse Oil Total	13.05 mL	Volume Oil Total	28.85 mL
Tank Configuration	A Only	Tank A Conditioner	Your choice	Tank B Conditioner	Your choice

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	18	148	0.0	7.6	7.6	7400
2	5L	5R	2	18	62	7.6	12.7	5.1	3100
3	10L	10R	2	18	42	12.7	17.8	5.1	2100
4	10L	10R	2	22	42	17.8	24.0	6.2	2100
5	15L	15R	2	22	22	24.0	30.2	6.2	1100
6	2L	2R	0	26	0	30.2	40.0	9.8	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	22	0	40.0	32.0	-8.0	0
2	15L	15R	1	22	11	32.0	28.9	-3.1	550
3	10L	10R	3	18	63	28.9	21.3	-7.6	3150
4	10L	10R	3	18	63	21.3	13.7	-7.6	3150
5	5L	5R	4	18	124	13.7	3.5	-10.2	6200
6	2L	2R	0	18	0	3.5	0.0	-3.5	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Created by SWEBOWL TK(HJ) 250618

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.03	1.44	1.06	1.06	1.44	3.03

