

Oil Pattern Distance	40	Reverse Brush Drop	35	Oil Per Board	50 ul
Forward Oil Total	17.7 mL	Reverse Oil Total	8.35 mL	Volume Oil Total	26.05 mL
Tank Configuration	Multi Tank	Tank A Conditioner	Valfri	Tank B Conditioner	Valfri

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	14	111	0.0	3.9	3.9	5550
2	6L	6R	1	14	29	3.9	5.8	1.9	1450
3	7L	7R	2	14	54	5.8	9.7	3.9	2700
4	8L	8R	2	18	50	9.7	14.8	5.1	2500
5	9L	9R	2	18	46	14.8	19.9	5.1	2300
6	12L	12R	2	18	34	19.9	25.0	5.1	1700
7	13L	13R	2	18	30	25.0	30.1	5.1	1500
8	2L	2R	0	18	0	30.1	36.0	5.9	0
9	2L	2R	0	22	0	36.0	40.0	4.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	0	40.0	28.0	-12.0	0
2	11L	11R	3	22	57	28.0	18.7	-9.3	2850
3	10L	10R	2	22	42	18.7	12.5	-6.2	2100
4	5L	5R	1	18	31	12.5	10.0	-2.5	1550
5	2L	2R	1	18	37	10.0	7.5	-2.5	1850
6	2L	2R	0	14	0	7.5	0.0	-7.5	0

Cleaner Ratio Main Mix	NA	Forward
Cleaner Ratio Back End Mix	NA	Reverse
Cleaner Ratio Back End Distance	NA	Combined
Buffer RPM: 4 = 700 3 = 500 2 = 200 1 = 100		

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Track Zone Ratio	3.89	1.46	1	1	1.46	3.89

