

0 -

1 2

5

## Sammandrag 3 41 fot

				·				BUILT FOR BOWLING
Oil Pattern Distance 41		41 Reverse I	Reverse Brush Drop 41		Oil Per Board		50 ul	
Forward Oil Total 14.9 mL		9 mL Reverse 0	Dil Total	9.2 mL		ume Oil Total	24.1 mL	
Tank Configuration A-B		A-B Tank A C	Tank A Conditioner		Tan	k B Conditioner	N/A	
START STOP LOADS   1 2L 2R 4   2 9L 9R 2   3 11L 11R 2   4 13L 13R 2   5 15L 15R 2   6 17L 17R 2   7 2L 2R 0   START STOP LOADS   1 2L 2R 2   2 15L 15R 1   3 13L 13R 1   4 11L 11R 2	SPEED CROSSED 9   14 148 46   18 30 1   18 22 14 2   22 14 2 0   22 14 2 0   5PEED CROSSED 9   18 11 1   18 11 1   18 15 1   18 38 1   18 38 1   18 38 3   18 38 3   18 46 4   14 74 1	START   END   FEET   T.O.     0.0   5.9   5.9   74     5.9   9.8   3.9   23     9.8   14.9   5.1   19     14.9   20.0   5.1   15     20.0   25.1   5.1   11     25.1   31.3   6.2   7     31.3   41.0   9.7   9.7	IL 00 00 00 00 00 00 0 0 0 0 0					30 35 40 45 50 55
Cleaner Ratio Main	- Mix	NA	Forward					25
Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance		NA NA	Reverse Combined					5
Buffer RPM: 4 = 72 Created by SWEBO		= 200  1 = 50		-				
Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18	R:17R-13R	18L-18R:12R-8R	18L-18R:7R	(-3R
		Middle Track:Middle	Inside Track:Middle		nside Track	Middle:Middle Track		Track
Track Zone Ratio	3.67	2.04	1.15		1.15	2.04	3.67	
1500 1350 1200 1050 900 750 600 450 300 150 								