

Oil Pattern Distance	43	Reverse Brush Drop	38	Oil Per Board	50 uI
Forward Oil Total	14.55 mL	Reverse Oil Total	10.85 mL	Volume Oil Total	25.4 mL
Tank Configuration	Multi Tank	Tank A Conditioner	KEGEL	Tank B Conditioner	KEGEL

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	3	18	111	0.0	5.1	5.1	5550
2	6L	6R	1	18	29	5.1	7.6	2.5	1450
3	7L	7R	1	18	27	7.6	10.1	2.5	1350
4	9L	8R	2	18	48	10.1	15.2	5.1	2400
5	11L	9R	2	18	42	15.2	20.3	5.1	2100
6	12L	10R	1	18	19	20.3	22.8	2.5	950
7	14L	12R	1	18	15	22.8	25.3	2.5	750
8	2L	2R	0	22	0	25.3	34.0	8.7	0
9	2L	2R	0	30	0	34.0	43.0	9.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	43.0	29.0	-14.0	0
2	11L	11R	3	22	57	29.0	19.7	-9.3	2850
3	9L	9R	2	22	46	19.7	13.5	-6.2	2300
4	8L	8R	2	18	50	13.5	8.4	-5.1	2500
5	7L	7R	1	18	27	8.4	5.9	-2.5	1350
6	2L	2R	1	14	37	5.9	4.0	-1.9	1850
7	2L	2R	0	10	0	4.0	0.0	-4.0	0

Cleaner Ratio Main Mix                      NA              Forward  
 Cleaner Ratio Back End Mix                NA              Reverse  
 Cleaner Ratio Back End Distance          NA              Combined  
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Bredd SM 2025. Created by SWEBOWL TK 200305.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.17	1.39	1.01	1	1.23	4.17

