

Oil Pattern Distance	39	Reverse Brush Drop	36	Oil Per Board	50 ul
Forward Oil Total	12.05 mL	Reverse Oil Total	14.3 mL	Volume Oil Total	26.35 mL
Tank Configuration	A Only	Tank A Conditioner	Your choice	Tank B Conditioner	Your choice

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	1	14	37	0.0	0.0	0.0	1850
2	4L	4R	1	14	33	0.0	1.9	1.9	1650
3	6L	6R	2	18	58	1.9	7.0	5.1	2900
4	8L	8R	2	22	50	7.0	13.2	6.2	2500
5	10L	10R	3	22	63	13.2	22.5	9.3	3150
6	2L	2R	0	26	0	22.5	39.0	16.5	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	22	0	39.0	33.0	-6.0	0
2	14L	14R	1	18	13	33.0	30.5	-2.5	650
3	12L	12R	3	18	51	30.5	22.9	-7.6	2550
4	9L	9R	2	18	46	22.9	17.8	-5.1	2300
5	7L	7R	3	18	81	17.8	10.2	-7.6	4050
6	5L	5R	2	14	62	10.2	6.3	-3.9	3100
7	4L	4R	1	14	33	6.3	4.4	-1.9	1650
8	2L	2R	0	10	0	4.4	0.0	-4.4	0

Cleaner Ratio Main Mix NA Forward  
 Cleaner Ratio Back End Mix NA Reverse  
 Cleaner Ratio Back End Distance NA Combined  
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Created by SWEBOWL TK(W) 250618.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.04	1.31	1.01	1.01	1.31	4.04

