


Oil Pattern Distance	42	Reverse Brush Drop	42	Oil Per Board	50 ul
Forward Oil Total	14.85 mL	Reverse Oil Total	7.05 mL	Volume Oil Total	21.9 mL
Tank Configuration	Only A	Tank A Conditioner		Tank B Conditioner	

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	4	14	148	0.0	5.9	5.9	7400
2	5L	5R	1	14	31	5.9	7.8	1.9	1550
3	6L	7R	1	18	28	7.8	10.3	2.5	1400
4	8L	9R	1	18	24	10.3	12.8	2.5	1200
5	9L	10R	1	18	22	12.8	15.3	2.5	1100
6	11L	12R	1	18	18	15.3	17.8	2.5	900
7	13L	14R	1	18	14	17.8	20.3	2.5	700
8	14L	15R	1	18	12	20.3	22.8	2.5	600
9	2L	2R	0	22	0	22.8	33.0	10.2	0
10	2L	2R	0	30	0	33.0	42.0	9.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	42.0	22.0	-20.0	0
2	13L	12R	2	18	32	22.0	16.9	-5.1	1600
3	11L	10R	1	18	20	16.9	14.4	-2.5	1000
4	8L	7R	2	14	52	14.4	10.5	-3.9	2600
5	2L	2R	1	10	37	10.5	9.1	-1.4	1850
6	2L	2R	0	10	0	9.1	0.0	-9.1	0



Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined

Buffer RPM: 4 = 720 | 3 = 500 | 2 = 200 | 1 = 50
 Created by Swebowl TK 230615(W)For use in Swedish league 2023

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	Middle:Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	2.83	1.47	1.01	1.04	1.47	2.74

