

Oil Pattern Distance	39	Reverse Brush Drop	37	Oil Per Board	50 uL
Forward Oil Total	11.9 mL	Reverse Oil Total	12.1 mL	Volume Oil Total	24 mL
Tank Configuration	A Only	Tank A Conditioner	ICE	Tank B Conditioner	FIRE

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	14	74	0.0	1.9	1.9	3700
2	6L	6R	1	14	29	1.9	3.8	1.9	1450
3	8L	8R	1	14	25	3.8	5.7	1.9	1250
4	10L	10R	3	14	63	5.7	11.6	5.9	3150
5	12L	12R	2	18	34	11.6	16.7	5.1	1700
6	14L	14R	1	18	13	16.7	19.2	2.5	650
7	2L	2R	0	18	0	19.2	26.0	6.8	0
8	2L	2R	0	26	0	26.0	32.0	6.0	0
9	2L	2R	0	30	0	32.0	39.0	7.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	39.0	32.0	-7.0	0
2	13L	13R	2	22	30	32.0	25.8	-6.2	1500
3	11L	11R	2	18	38	25.8	20.7	-5.1	1900
4	9L	9R	2	18	46	20.7	15.6	-5.1	2300
5	7L	7R	2	18	54	15.6	10.5	-5.1	2700
6	2L	2R	2	18	74	10.5	5.4	-5.1	3700
7	2L	2R	0	14	0	5.4	0.0	-5.4	0

Cleaner Ratio Main Mix NA Forward
 Cleaner Ratio Back End Mix NA Reverse
 Cleaner Ratio Back End Distance NA Combined
 Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Created by SWEBOWLK TK 240825 For use In Swedish league 2024->
 Machines without db uses db 39.

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	4.17	1.59	1.01	1.01	1.59	4.17

